



Features

- Die-cast aluminium housing
- 15" TFT LCD panel, 1024x768
- Support VGA and HDMI, incl. Speaker
- Flat Screen Front Panel, foldable metal stand
- VESA Standard 75x75mm and 100*100mm
- Multi-point projected capacitive touch screen

Technical Specification

Screen Size	15"
Backlight	LCD
Aspect Ratio	4:3
Active Area (mm)	304.128 (H) x 228.096 (V)
Max. Resolution	1024 x 768
Brightness	500 cd/m2 (Panel Typ.)
Pixel Pitch (mm)	0.0642 (H) x 0.1709 (V)
Contrast Ratio (Typ.)	1000:1
Viewing Angle (H x V)	170° x 170°
Display Color	16.7 M Colors
Response Time (Tr/Tf) (Typ.)	25 ms
Video Input	1x VGA, 1x HDMI, 1x USB (touch), 1x Audio
Power Input	DC 12V
Power Consumption	Max. 20W
Operating Condition	Temp: -20°C ~ 70°C, Hum.: 10 ~ 90%
Storage Condition	Temp: -20°C ~ 70°C, Hum.: 10 ~ 90%
Touch Panel	PCAP Touch
Certificates	CE, ROHS
In Box	1x Monitor, 1x HDMI cable, 1x USB cable, 1x Power Adapter